**Our Product Introduction** 

for more products please visit us on enookbattery.com

# lifepo4 square battery 3.2V 280ah 305ah 100ah 200ah green lifepo4 cell for golf carts



### **Product Specification**

- Storage Temperature: 0 ~35
- Weight: 1920±100G

• OEM/ODM: Yes(Accepted)

- Charging Temperature: 0 ~65
- Standard Charge- 0.5C(P) discharge Rate:
- Discharging -35 ~65 Temperature:
- Cycling Performance: 6000 Cycles ~4000 Cycles
- Standard Rating Cycle: 2000 (0.5C/0.5C)
  - 3.2V lifepo4 square battery, 280ah lifepo4 square battery, 305ah lifepo4 square battery









### More Images

• Highlight:



### **Product Description:**

At a size of 118.5(H)\*160(W)\*50.1(T), this battery is a compact and efficient option that won't take up too much space. However, despite its small size, it packs a powerful punch, thanks to its 3.2V 280Ah Lifepo4 Battery. This high-quality battery features 100% NEW A-grade Cells, ensuring that you get the best performance possible.

Despite its impressive power, this battery is surprisingly lightweight, weighing in at just 1920±100G. This makes it highly portable and easy to carry around, even if you are using it in a device that needs to be moved frequently.

Basic Information								
Model	202Ah	230Ah	240Ah	280Ah	LF280K			
Size(mm)	174*207*54	174*207*5 4	173*204*7 2	173*207*72	173*207*72			
Weight(kg)	4.2	4.45	5.35	5.5	5.5			
Cycle life	6000 Cycle							
Warranty	3-5 Years							
BMS	Support JK, Daly BMS.,etc. Support 4S(12V 100A-200A), 8S(24V 100A-200A), 16S(48V 100A-200A,. etc)							
Packaging	4pcs/carton, with EVA foam and waterproof package bag							
Shipping time	Poland & Germany stock, 3-5 working days; CN stock, 35-45 working days(by sea)							
Operation								
Standard Voltage	3.22V							
Internal Resistance	≤0.25mQ							
Standard charge current	40.4A(0.2C)	46A(0.2C)	48A(0.2C)	56A(0.2C)	56A(0.2C)			
Max. charge current	202A(1C)	230A(1C)	240A(1C)	280A(1C)	280A(1C)			
Standard discharge current	0.2C							
Max discharge current	1C							
Operating temperature	Charging: 0 °C ~45 °C; Discharging: -20 °C ~60 °C							

### Large Stock



# Overseas warehouses

Product Advantages



### **Features:**

Product Name: 3.2v 280ah LifePo4 Lithium Ion Battery Package: ABS/Metal Case Or OEM Weight: 1920±100G Cycling Performance: 6000 Cycles ~4000 Cycles Standard Charge-discharge rate: 0.5C(P) Size: 118.5(H)\*160(W)\*50.1(T) Approx. Weight of 60v battery pack: 4.0~40.0kg



### **Technical Parameters:**

OEM/ODM:	Yes(Accepted)
Storage Temperature:	0 ~35
Package:	ABS/Metal Case Or OEM

Charging Temperature:	0~65
Standard Charge-discharge rate:	0.5C(P)
Discharging Temperature:	-35 ~65
Weight:	Approx. 4.0~40.0kg
Size:	118.5(H)*160(W)*50.1(T)
Capacity:	Customized
Battery Type:	3.2V 280Ah Lifepo4 Battery

### Stable

Product Advantages

Low IR / High CR / Discharge Steadily / Environmentally Friendly/Super Long



# **Model List & Parameters**

Product Advantages

Model	Voltage (V)	Capacity (Ah)	Cycles (Ah)	Initial IR (≤mΩ)	Weight (g)	Height (m m )	Width (m m )	Thickness (mm)
Lf32	3.20	32	3500 (0.5C/0.5C)	1.5	730±50	94.3±0.5	148.3±0.8	26.7±0.5
LF50F	3.20	50	1500 (0.5C/0.5C)	2.0	1035±100	129.8±0.5	148.3±0.5	26.7±0.5
LF90K	3.20	90	6000 (1c/1C)	0.5	1994 <u>±</u> 50	200.5 <u>±</u> 0.5	130.3 <u>±</u> 0.3	36.7±0.5
LF100MA	3.20	101	2000 (0.5C/0.5C)	0.5	1920±100	118.5±0.5	160.0±0.8	50.1±0.5
LF100LA	3.20	102	5000 (0.5C/0.5C)	.0.5	1985±100	118.5±0.5	160.0±0.8	50.1±0.5
Lf105	3.20	105	4000 (0.5C/0.5C)	0.32	1980±60	200.5±0.5	130.3±0.5	36.35±0.5
Lf160	3.20	160	4000 (0.5C/0.5C)	0.21	3000±100	153.5±0.5	173.9±0.5	53.85±0.5
Lf173	3.20	173	4000 (0.5C/0.5C)	0.25	3190 <u>+</u> 96	207.5±0.5	173.9±0.5	41.06±0.5
Lf230	3.20	230	4000 (0.5C/0.5C)	0.2	4140±124	207.2 <u>±</u> 0.5	173.9 <u>±</u> 0.5	53.85 <u>±</u> 0.5
LF280K	3.20	280	6000 (0.5C/0.5C)	0.25	5420±300	207.2±0.5	173.7+0.5	72.0+1.0
Lf304	3.20	304	4000 (0.5C/0.5C)	0.16	5450±164	207.2 <u>±</u> 0.5	173.7±0.5	71.70.8

# Certificate

Product Advantages



#### **Applications:**

The enook 3.2V Lifepo4 Lithium lon Battery is perfect for use in electric bikes, mountain bikes, motorcycles, and bicycles. Its capacity can be customized to meet the needs of the user.

This battery is designed with a standard charge-discharge rate of 0.5C(P), ensuring that it can be charged and discharged safely and efficiently. It comes packaged in an ABS/metal case or can be customized according to the user's specific needs.

The enook 3.2V 280ah Lifepo4 Lithium Ion Battery is suitable for use in various occasions and scenarios. It is a perfect choice for individuals who require a reliable and efficient power source. Its compact and lightweight design make it easy to install and use, while its customizable voltage and capacity options ensure that it can be used in different applications.

In summary, the enook 3.2V Lifepo4 Lithium Ion Battery is a high-quality product that is perfect for use in different scenarios. Its versatility, customizable voltage and capacity options, and standard charge-discharge rate make it a reliable and efficient power source for various applications. Whether you need a lithium E-bike battery for your electric bike, mountain bike, motorcycle, or bicycle, this battery is the perfect choice.

### Our products have a very widely range of use



#### **Customization:**

Looking for a reliable and high-performance battery for your e-bike? Look no further than enook's 3.2V Lifepo4 Lithium Ion Battery! Made in China with top-quality materials and expert craftsmanship, this battery is designed to meet your needs and exceed your expectations. With a standard rating cycle of 2000 (0.5C/0.5C), this battery is built to last, providing you with reliable power and performance every time you need it. And with customizable voltage and capacity, you can tailor this battery to your specific needs and preferences. Whether you prefer an ABS/metal case or an OEM package, enook has you covered. And with cycling performance of up to 6000 cycles, you can trust that this battery will keep you going for years to come.



### Support and Services:

Our LifePo4 Lithium Ion Battery product comes with comprehensive technical support and services to ensure our customers have a hassle-free experience:

- We provide product installation and configuration guidance to help you set up and use the battery effectively.
- Our technical team is available to answer any questions or concerns you may have about the product.
- We offer troubleshooting and repair services to resolve any issues you may encounter with the battery.
- Our warranty ensures that any defects or malfunctions with the battery will be addressed promptly and effectively.



The default that 1pc cell come with 1 bus bar and 2pcs bolt, if you need more, please contact us.

# PACKAGING

Product Advantages



ROOM 1717, JIEZUO BUILDING, NO. 828, SECTION 1, FURONG SOUTH ROAD, TIANXIN DISTRICT, CHANGSHA, HUNAN